



Water can become electrified at any time. Pools and docks are surrounded by lights, pumps, boat lifts, etc. Faulty wiring, failed GFCI's, or stray voltage can introduce electricity to the water where your family swims. When this low level AC current passes through the body with enough force to cause paralysis, THIS CAN RESULT IN DROWNING – ELECTRIC SHOCK DROWNING

PREVENT ELECTRIC SHOCK DROWNING BY TESTING THE WATER WITH SHOCK ALERT



HOW DOES SHOCK ALERT WORK?

Shock Alert is a device that uses three (3) probes to detect voltage gradients in water and warn you and your family of potentially dangerous electricity.







FLASHING WARNING INDICATORS

If there is voltage present in the water, the Shock Alert will flash red LED warning lights.



AUDIBLE WARNING INDICATORS

The Shock Alert is equipped with audible warning indicators that beep loudly when electricity is detected in the water.



INCREASING WARNING INDICATORS

As you move closer to the voltage source, the intensity of visible and audible warnings will increase.

WHERE SHOULD SHOCK ALERT BE USED?

POOLS



DOCKS



FOUNTAINS







DEVICE SPECIFICATIONS

| SKU # | 42500 |
|------------------------------------|---|
| Size (HxWxL) | 5.25 in x 8.5 in x 9.5 in |
| | (13.3 cm x 21.6 cm x 24 cm) |
| Weight | 1.9 lbs (862 grams) |
| Battery Type | Three (3) AA Batteries (Batteries Not Included) |
| Max Electricity Withstand in Water | 120V AC (Measurement Category II) |

PARTS LIST:

- Shock Alert Device (1)
- 12' Rope Tether (1)

NOTE: Three (3) AA batteries are required for operation of this device. Batteries are NOT included.

OPERATION INSTRUCTIONS

Do not operate device prior to reading complete operation instructions located inside the Owner's Manual.

This device is designed to detect electricity present in water by measuring the voltage gradients using the three probes located on the bottom of the device. It is NOT designed to and WILL NOT absorb electrical voltage from the water. WARNING: Use extreme caution and avoid contact with water until Shock Alert shows no voltage detected.

- 1. Remove battery cover and insert three (3) AA batteries according to instructions on the battery packaging. Replace battery cover.
- 2. Attach 12' tether to the Shock Alert device.
- 3. Power on the device and run through Self-Test mode.
- 4. Using the rope tether, lower device into water.
- 5. Device will flash green if there is no voltage present. Device will flash red and beep if voltage is present. As you move closer to the voltage source, the flashing and beeping will increase.
- 6. Using the rope tether, pull the Shock Alert around the perimeter of the pool, dock, fountain, etc.

REV B 03/18



1-844-NO-SHOCK www.shockalert.com SHOCK ALERT, LLC.

50 N. CENTRAL DRIVE, O'FALLON, MO 63366